

May 2, 2022

Klüber Lubrication NA LP • 9010 CR 2120 Tyler, Texas 75707 • Phone 903.534.8021 • sales@klsummit.com

# Product Data Sheet



**NOTE:** The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

## SYNTHETIC SYSTEM FLUSH

### Flushing Oil

*Summit Flushing Oil is a diester based product designed for flushing lubricant circulating systems. It has excellent detergency, dispersancy, and biodegradability properties. Flushing Oil is not recommended as an operational fluid. To use Flushing Oil, open the air end and run equipment until it gets warm, under no load. To flush a loaded system DSL®-100S is recommended.*

### Physical Properties

PRODUCT	Flushing Oil
Specific Gravity	.967
Viscosity:	
@ 40°C, cSt	38
@ 100°C, cSt	5.4
Viscosity Index	62
Pour Point, °F (°C)	-43.6 (-42)
Flash Point, °F (°C)	435 (224)

**Shelf Life:** Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.